

DURACELL®

TECHNICAL DATA SHEET

Type no.	DP 140
Article no.	010640350801
EAN/GTIN no.	9005753086289
Application	Starter battery
Electrical data	
Rated voltage	12V
Rated capacity	140 Ah (K20)
Cold start current	760 A (EN)
Dimensions and weights	
Box	A
Length max.	513mm
Width max.	189mm
Box height max.	195mm
Total height max.	220mm
Battery weight	Ca. 34,00 kg (+/- 5 %)
Electrolyte density	Approx. 1,28 kg/l
Electrolyte	Diluted sulphuric acid
Items/pallet	24
Pallet ID	Euro pallet
Items per layer	8
Features	
Base hold-down	B00
Layout	3
Terminal	1
Separator	PE bag separator
Degassing	Battery with single degassing
Flame arrester	Not integrated
Performance identification	W4-C2-V2-E1
Maintenance ¹⁾	
Water consumption	W4
Refill water	Distilled or demineralised (DIN 43530)
Self-discharge	Approx. 3 % per month
Charging current	Approx. 1/10 of the rated capacity
Charging voltage ²⁾	max. 14,8 V



¹⁾ All the listed values relate to room temperature +25° C

²⁾ Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!

