

DURACELL®

TECHNICAL DATA SHEET

Type no.	DP 110
Article no.	010610470801
EAN/GTIN no.	9005753088801
Application	Starter battery
Electrical data	
Rated voltage	12V
Rated capacity	110 Ah (K20)
Cold start current	800 A (EN)
Dimensions and weights	
Box	COMPACT
Length max.	344mm
Width max.	172mm
Box height max.	214mm
Total height max.	230mm
Battery weight	Ca. 29 kg (+/- 5 %)
Electrolyte density	Approx. 1,28 kg/l
Electrolyte	Diluted sulphuric acid
Items/pallet	36
Pallet ID	Euro pallet
Items per layer	12
Features	
Base hold-down	B00
Layout	0
Terminal	1
Separator	PE bag separator
Degassing	Battery with single degassing
Flame arrester	Not integrated
Performance identification	W3 - C2 - V2 - E1
Maintenance 1)	
Water consumption	W3
Refill water	Distilled or demineralised (DIN 43530)
Self-discharge	Approx. 5 % per month
Charging current	Approx. 1/10 of the rated capacity
Charging voltage 2)	max. 14,4 V



1) All the listed values relate to room temperature +25° C

2) Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!

