



PS Range

(5yr Design Life in Float Service at 20°C)

Dimensions (mm)



Standard terminal (mm)



Physical Specification

Nominal Voltage		12V
Nominal Capacity (20HR)		2.1 AH
Dimension	Length	178 ± 2 mm
	Width	35 ± 2 mm
	Container Height	60 ± 2 mm
	Total Height (with terminal)	66 ± 2 mm
Weight		Approx 0.96kg
Standard Terminal		F1

PS-1221 12V 2.1AH



Discharge Characteristics (25°C, 77°F)

Rated Capacity	20hr Rate(1.80V/cell) 10hr Rate(1.80V/cell) 5hr Rate(1.75V/cell) 3hr Rate(1.75V/cell) 1hr Rate(1.60V/cell)	2.30AH 2.14AH 1.93AH 1.69AH 1.40AH	Constant Voltage Charge	Cycle	Initial Charging Current Less than 0.575A Voltage 14.40V ~ 15.0V at 25°C (77°F)
Capacity Affected by Temperature	40°C (104°F) 25°C (77°F) 0°C (32°F)	103% 100% 86%		Standby	Recommended Charge Current less than 0.52A Voltage 13.5V ~ 13.8V at 25°C (77°F)

Internal Resistance mΩ


90.0 mΩ

Constant Current Discharge Characteristics Unit: Amperes (25°C, 77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	4.42	3.08	2.54	2.20	1.77	1.36	1.11	0.679	0.517	0.425	0.361	0.312	0.248	0.207	0.114
1.80V/cell	5.43	3.67	2.94	2.49	1.96	1.48	1.20	0.721	0.544	0.447	0.376	0.326	0.258	0.214	0.115
1.75V/cell	6.43	4.15	3.25	2.71	2.09	1.57	1.26	0.752	0.563	0.461	0.386	0.334	0.265	0.218	0.116
1.70V/cell	7.30	4.58	3.51	2.91	2.19	1.63	1.31	0.783	0.581	0.472	0.396	0.342	0.269	0.222	0.118
1.65V/cell	8.05	4.93	3.72	3.06	2.29	1.70	1.37	0.806	0.596	0.482	0.405	0.349	0.273	0.225	0.120
1.60V/cell	8.45	5.13	3.87	3.15	2.35	1.74	1.40	0.831	0.610	0.494	0.413	0.356	0.279	0.229	0.121

Constant Power Discharge Characteristics Unit: (Watts/cell) (25°C, 77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	8.33	5.86	4.88	4.27	3.45	2.66	2.19	1.34	1.03	0.848	0.722	0.627	0.500	0.416	0.230
1.80V/cell	10.1	6.93	5.61	4.79	3.79	2.89	2.34	1.42	1.07	0.886	0.748	0.650	0.515	0.428	0.231
1.75V/cell	11.8	7.76	6.13	5.17	4.02	3.05	2.45	1.47	1.11	0.908	0.764	0.662	0.526	0.434	0.232
1.70V/cell	13.3	8.46	6.58	5.51	4.19	3.15	2.54	1.52	1.14	0.925	0.778	0.674	0.530	0.439	0.235
1.65V/cell	14.5	8.99	6.87	5.73	4.33	3.25	2.63	1.56	1.16	0.940	0.792	0.684	0.536	0.443	0.237
1.60V/cell	14.9	9.24	7.08	5.84	4.41	3.29	2.67	1.60	1.18	0.957	0.803	0.694	0.545	0.448	0.237



BATTERY CHARGED
Unit 17
M11 Business Link
Stansted
Essex
CM24 8GF

Tel: 03300 412187
www.batterycharged.co.uk
email: info@batterycharged.co.uk