



SB12V25P-SC

Lightweight Lithium Ion starter battery, 9,26 lb / 4.2 kg, specially developed for racing cars up to 6 litre using alternator.

Safety

super B batteries are based on Lithium Iron Phosphate technology (LiFePO4). This Lithium Ion technology used in super B batteries is the safest Lithium Ion technology available today. On top of that our bespoke casing and electronics further increase safety and durability.



Applications for SB12V25P-SC

DTM	Group C	WRC
BTCC	WTCC	NASCAR
LMS	GT's	GT Endurance
Dakar Rally Raid	Britsports	ALMS
4x4		

Super B Lithium batteries to perform better

Diamantstraat 1e 7554 TA Hengelo The Netherlands +31 (0)748200010

- F +31 (0)74 820001
- E info@super-b.com

Technical specifications SB12V25P-SC

SKU/EAN13	8718531360082
Battery Designation	4IFP97/250/142-10
Height (mm)	140,30 / 141,30
Diameter (mm)	NA
Width (mm)	248,35 / 249,35
Thickness (mm)	95,25 / 96,25
Nominal voltage (V)	13,2V
Charge method	CCCV
End of charge voltage (V)	15,2V
End of charge voltage (V) for endurance (cycle life)	14,4V
Charge current (A)	100A (4C)
Charge current (A) for endurance (cycle life)	30A (1C)
End-of-discharge voltage (V)	8V
?End-of-discharge voltage (V) for endurance (cycle life)	10V
Discharge current (A)	700A (30C)
Discharge current (A) for endurance (cycle life)	23A (1C)
Discharge pulse current (A) (10 seconds)	1200A (52C)
Discharge pulse current (A) (1 second)	1500A (65C)
Discharge performance at 20 °C (rated capacity)	23Ah / 303,6Wh
Discharge performance at -20 °C (capacity)	20,7Ah / 273,24Wh
High rate discharge performance at 20 °C (capacity)	21,85Ah / 288,42Wh
EqPb (Equals Lead acid battery)	100 to 130Ah
Operating temperature range	-30°C to +60°C

Super B Lithium batteries to perform better

SU

F +31 (0)74 8200010

E info@super-b.com



Storage temperature range	-50°C to +60°C
Weight	4,2kg


Super B Lithium batteries to perform better


Diamantstraat 1e 7554 TA Hengelo The Netherlands +31 (0)748200010

- F +31 (0)74 820001
- E info@super-b.com



Performance of the SB12V25P-SC





Super B Lithium batteries to perform better

Diamantstraat 1e 7554 TA Hengelo The Netherlands +31 (0)748200010

- F +31 (0)74 820001
- E info@super-b.com