

Yuasa Technical Data Sheet

\* Due to unprecedented demand following the easing of COVID-19 lockdown measures, this product may be supplied without a state of charge indicator and not conform to the level of roll over protection advertised. Product performance and quality are not affected by this. Please check battery labels for specification details.

#### Yuasa YBX7096 - YBX7000 EFB Start Stop Plus Batteries

#### Performance

Voltage12VCapacity (20-hour)75AhCold Cranking Amps (EN1)700A

# **Dimensions**

Length	278mm
Width	175mm
Height	190mm

### **Weights & Measures**

Mean Weight with Acid

# **Container Features**

Case Type	L3 DIN EFB
Hold Down	B3
State of Charge Indicator	✓
Handles	✓
End Venting	✓
Lid Type	SMF Double Lid

19.3kg



# Technology

Flame Arrestor	✓
Technology	Ca/Ca
Separator	PE
VDA Roll Over Test	✓
Recommended Charge Rate	4A
Performance Marking	W3-C2-V3-M1

# Terminal TypeCell Assembly LayoutBattery Hold-downT1<br/>Standard DIN Post<br/> $\downarrow 0 19.5 \downarrow$ $\downarrow 0 17.9 \downarrow$ $\downarrow 0 17.9 \downarrow$ $\downarrow 0 17.9 \downarrow$ $\downarrow 0 17.9 \downarrow$ Positive TerminalNegative TerminalNegative TerminalNegative Terminal

Data Sheet generated on 10/09/2024 – E&OE

#### The world's leading battery manufacturer



YUAS/